

CW9000 Range



CW9000 - Wireless Control Panel

Overview

Using Cooper wireless protocol the wireless control panel (CW9000) provides a fire detection system using secure wireless connections between the field devices and the control panels.

Based on well proven components the sensors, sounders, beacons and callpoints give CW9000 a highly reliable foundation into which the wireless technology has been integrated to provide a fully featured intelligent addressable fire detection and alarm system.

The development of CW9000 has tracked the progress of the European Standard EN54-25 "Fire detection and fire alarm systems. Components using radio links", and has therefore been designed to conform fully with all aspects of this document.

Features


- Meets the requirements of EN54 Pt25
- Address capacity up to 250 wireless devices
- Range > 1km in free air
- Soft addressing
- Multi-language selection capability
- Monitor battery status under all conditions
- Large versatile touch-screen user interface

Benefits

- Simple to operate end user touch-screen interface
- Eliminates difficulties and costs associated with wired fire systems
- Minimise disruption
- Helps preserve building aesthetics
- Full system integrity with Cooper developed protocol

Wireless Control Panel - CW9000 Range

Dimensions




	H (mm)	W (mm)	D (mm)
Panel	375	357	95
Aerials	85	85	

Technical Specification

Code	CW9000
Description	Wireless Control Panel
Standards	EN54 Pt25
Power	
Operating Voltage	230V ac +10%/-15% (nom)
Current Consumption	75mA (nom)
Mains Fuse	1.6A slow blow
Batteries	
Number	2
Manufacturer	Yuasa, YSP12-4
Capacity	4Ah
Battery Fuse (F4)	4A quick blow
Battery Current	3.5A (max)
Standby Current	(mA) 100 (1 loop)
Wireless Capacity	
Address Capacity	250 devices (max)
Wireless Outputs	60 sounders + 20 3 channel input/outputs
Environmental	
Operating Temperature	-10°C to +55°C
Humidity (Non Condensing)	0 to 95% RH
Physical	
Construction	Back box - mild steel (powder coated) Fascia - PC/ABS
Colour	Graphite
Dimensions (H x W x D)	375mm x 375mm x 95mm
Weight (incl. batteries)	9kg
Weight (excl. batteries)	4kg
Cable Knockouts	11mm x 20mm
Flammability Rating	UL 94 V0
Compatibility	
Suitable for use with	Cooper Wireless Fire Systems

Standard Connection



Product Codes

Code	Description
CW9000	Wireless Control Panel

Descriptions represent only particulars of the goods to which they apply and do not form part of any contract. The company reserves the right to change specification without prior notification or public announcement.

Cooper Lighting and Safety Ltd, Wheatley Hall Road, Doncaster, South Yorkshire, DN2 4NB. UK.

T: +44 (0) 1302 303350 | F: +44 (0) 1302 303332 | E: techsupport@cooperfire.com | W: www.cooperfire.com