

ULFPTR6000 Network Repeater Panel, Touch Screen



Overview

The ULFPTR6000 repeater panel provides sophisticated 'touch screen' functionality yet achieves a simple end-user interface operation within a compact panel design.

The ULFPTR6000 is designed to work with all UL Listed JSB analogue fire alarm control panels as a network repeater. The JSB 'touch-screen' repeater panel is easy to install and commission. All text is transmitted via the network and is automatically updated.

Features

- Plug and play. All information is downloaded through the network
- Touch-screen display
- Integrated network capability allows networking with the latest JSB range of analogue fire alarm control panels
- Multi language capability
- PSU approved to EN54 pt4 and UL864 9th Edition
- Up to 126 repeaters can be connected to the network
- Programmable as an active or passive repeater
- Dual redundant network card to enhance system integrity


Benefits

- Plug and play requires no programming
- Easy to operate touch screen display
- System integrity, fire alarm system continues to operate even if there is a short circuit or open joint on cable
- Easy to change the language to suit the operator


Technical Specification

Code	ULFPTR6000
Description	Repeater Panel, Touch Screen
Standards	UL864 9 th edition, NFPA 70-72
System Indicators	
LED's	Power on, Alarm, General Trouble, General Supervisory, Power Trouble, System Trouble, Test, NAC Trouble.
Mains Input, Supervised, Power Limited	
Voltage	120 V ac to 240 V ac, 60 Hz
Current	100 mA
Network SLC	5 V dv, 11 mA (max)
Line impedance	50 ohm (max)
Batteries	
Batteries	2x12 V dc, 7 Ah, 0.1 derating
Battery Charge Current	1.0 Amp
Standby Period	24 hours + 30min. alarm
Programmable Relay	
Programmable Relay (Fire)	30 V, 1 A, Resistive
Download Comms	
Download Comms	RS232 port
Environmental	
Operating Temperature	0°C to 49°C
Humidity (Non Condensing)	0 to 93 %RH
Physical	
Dimensions (H x W x D)	395mm x 332mm x 115mm
Weight	9kg (with batteries) 4kg (without batteries)
Ingress Protection	IP40
Construction	PC/ABS, UL94 5VA rating
Colour	Graphite
Display	Touch Screen
Cable Entry	11 x 20mm knockouts top of backbox
Compatibility	
Suitable for use with	JSB UL analogue addressable fire systems

Mounting the Backbox



Dimensions



H (mm)	W (mm)	D (mm)
395	332	115

Product Codes

Code	Description
ULFPTR6000	Repeater Panel, Touch Screen